

Dimensions

117 × 74 mm

Pack Size

1

Weight

-

Material

High Impact Poly Carbonate

Technical Data

Rating - 230-250Va.c. 50Hz,
Load, 20 Amp RCD, Protection -
30mA, Trip Time - < 100mS

Standards

AS/NZS3000
AS/NZS3190

Description

Residual Current Device (RCD)
Horizontal 240V a.c. 20 Amp
30mA c/w Circuit Identification
Provision, 'Power Available' and
'Line Power' indicators

Colour

Dark Blue (DB)
Red (RD)
White (WH)

Orientation

Horizontal

PART NO	COLOUR	DESCRIPTION
ESOMHR30WH		Residual Current Device (RCD) Horizontal 240V a.c. 20 Amp 30mA c/w Circuit Identification Provision, 'Power Available' and 'Line Power' indicators Available in the following Colours: White (WH) Red (RD) Dark Blue (DB)
ESOMHR30RD		
ESOMHR30DB		

Approved by	Name	Signature	Date
Contractor			
Consultant			
Architect			
Client			
Other			

HEAD OFFICE

89 Egerton St (Cnr Fariola & Egerton)
PO Box 6193
Silverwater, NSW 2128
Australia

CONTACT

Phone: 1300 879 363
Email: customer.service@escoindustries.com.au